

# WSB™ Weather Seal Strain Relief Boots

For LMR-240, LMR-400 & LMR-600

ISO 9001 Certified

- *Combination strain relief and weather seal boot*
- *Eliminates the need for a heat gun to shrink the standard heat shrink sleeve*
- *Fits the most popular LMR®-240, 400 & 600 EZ connectors*
- *IP-67 rated*
- *Convenient 10 pack*



The WSB™ weather seal strain relief boots work with the most popular EZ crimp connectors for LMR-240, 400 and 600.

The soft silicone boot weatherproofing kits replace older weatherproofing methods, require no heat and only simple and easy hand assembly for valuable time saving in the field.

The WSB™ weather seal strain relief boots are IP67 rated and both RoHS and REACH Compliant.

Supplied in a convenient 10 pack, the WSB™ kits contain four pouches of silicone lubricant to facilitate installation of the boots.



Australian Representatives  
**ROJONE, PTY LTD.**

Tel: 02 9829 1555  
E: [sales@rojone.com.au](mailto:sales@rojone.com.au)  
[www.rojone.com.au](http://www.rojone.com.au)

# WSB™ Weather Seal Strain Relief Boots

**Construction:**

Material: Silicone rubber  
 Color: Black  
 Lubricant: Silicone grease

**Ordering information:**

Part Number - Stock Code  
 WSB-240 3109-400  
 WSB-400 3109-394  
 WSB-600 3109-401

Mechanical/Environmental Specifications					
		Test Method	Value		
Hardness		DIN 53505	Shore A		
Density at 20°C		DIN 51757	1.19 g/cm <sup>3</sup>		
Elongation at Break		DIN 53504 S1	300%		
Rebound Resilience		DIN 53512	50%		
Tear Strength		ASTM D624-B	18 N/mm		
Compression Set		DIN ISO 815-B	12%		
Operating Temperature			-40°C to 85°C		
Connector Compatibility					
WSB-240		WSB-400		WSB-600	
Part #	Description	Part #	Description	Part #	Description
3190-2726	EZ-240-TM-RA-X	3190-2524	EZ-400-716M-X	3190-2642	TC-600-716M-X
3190-2868	EZ-240-BM-RA-X	3190-2597	TC-400-716M-X	3190-2546	EZ-600-716M-RA-X
3190-2893	EZ-240-NMH-X	3190-2545	EZ-400-716M-RA-X	3190-2816	TC-600-NF-X
3190-2894	EZ-240-QM-X	3190-2590	EZ-400-NMH-X	3190-2817	EZ-600-NF-X
3190-2897	EZ-240-SM-X	3190-2626	TC-400-NMH-X	3190-2627	EZ-600-NMH-X
3190-6143	EZ-240-NMH-RA-X	3190-2293	TC-400-NMH-RA-D	3190-2628	TC-600-NMH-X
3190-6204	EZ-240-TF-X	3190-3049	EZ-400-TF-X	3190-6123	EZ-600-QNM-X
3190-2896	TC-240-SF-BH-SS-X	3190-3051	TC-400-TF-X	3190-6136	TC-600-SCM-X
3190-2898	TC-240-SM-SS-X	3190-2533	EZ-400-TM-X	3190-3050	EZ-600-TF-X
		3190-2532	TC-400-TM-X	3190-3052	TC-600-TF-X
		3190-2800	EZ-400-TM-RA-X	3190-2531	EZ-600-TM-X
		3190-2818	EZ-400-NF-X	3190-2530	TC-600-TM-X
		3190-2815	TC-400-NF-X		
		3190-2803	EZ-400-NF-PM-X		
		3190-2805	TC-400-NF-PM-X		
		3190-2852	EZ-400-BM-X		
		3190-2847	EZ-400-BM-RA-X		
		3190-2961	EZ-400-NMH-PL-X		
		3190-2962	TC-400-NMH-PL-X		
		3190-2969	EZ-400-4195M-X		
		3190-2968	EZ-400-4195F-X		
		3190-2979	EZ-400-QNM-X		
		3190-2980	EZ-400-QNF-X		
		3190-2981	EZ-400-QNM-RA-X		
		3190-6011	EZ-400-QNF-BH-X		



World Headquarters: 358 Hall Avenue, Wallingford, CT 06492 • Tel: 203-949-8400, 1-800-867-2629 Fax: 203-949-8423

International Sales: +1 203-949-8503 • +1 800-867-2629

China Sales: TMC Building 4, No. 318 Yuanshan Road, Xinzhuang Industrial Park, Shanghai, China 201108 Tel: 86-21-5176-1209 Fax: 86-21-64424098  
[www.timesmicrowave.com](http://www.timesmicrowave.com)

© 2016, Times Microwave Systems, Wallingford, CT 06492

WSB-03/16